

PRODUCT DATA SHEET

SikaProof® Tape-120

Self-adhesive tape for internal jointing / detailing of SikaProof®-808 / -810

DESCRIPTION

SikaProof® Tape-120 is a self-adhesive tape based on a hotmelt adhesive with a carrier film and a release liner.

USES

- Sealing and bonding overlap joints, connections and details within the SikaProof®-808 / -810 membrane system

CHARACTERISTICS / ADVANTAGES

- Fully bonded to the concrete structure (same as SikaProof®-808)
- No lateral water underflow between the concrete structure and the membrane system
- High adhesion and sealing capability in cold and damp conditions
- Simple and fast to install

PRODUCT INFORMATION

Packaging	4 rolls packed in one cardboard box	
	Individual roll size	Length: 20 m Width: 120 (± 5) mm
Appearance / Colour	Top layer	Light grey A+ bonding layer with a grey waterproofing layer
	Bottom layer	Transparent/yellowish hotmelt adhesive covered with a release liner
Shelf life	18 months from date of production	
Storage conditions	The Product must be stored in original unopened and undamaged packaging in dry conditions and temperatures between +5 °C and +30 °C. Store in a horizontal position. Do not stack pallets of the rolls on top of each other, or under pallets of any other materials during transport or storage. Always refer to packaging.	
Thickness	0,60 mm	

SYSTEM INFORMATION

System Structure	<ul style="list-style-type: none"> ▪ SikaProof® -808/-810 sheet membrane system ▪ SikaProof® Tape-120 self-adhesive tape for internal jointing
-------------------------	--

APPLICATION INFORMATION

Ambient Air Temperature +5 °C min. / +45 °C max.

Substrate Temperature +5 °C min. / +60 °C max.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER DOCUMENTS

- Sika Method Statement: SikaProof®-808
- Product Data Sheet: SikaProof®-808/-810

IMPORTANT CONSIDERATION

Installation work must only be carried out by Sika® trained, approved or competent contractors experienced in this type of application.

- Do not install SikaProof® Tape-120 during continuous or prolonged rain or snowfall.
- The substrate quality and conditions must be fulfilled or appropriate measures must be taken. Contact Sika® Technical Services for more information.
- SikaProof® Tape-120 is not permanently UV resistant. The concrete must be placed within 60 days after the SikaProof®-808 membrane system has been installed.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The contact surface is the grey SikaProof®-808/-810 A+ bonding layer. It must be dry or slightly damp, clean and free of any materials that could impair adhesion. If the substrate requirements are not achieved, suitable measures must be taken. Contact Sika® Technical Services for more information.

APPLICATION METHOD / TOOLS

Strictly follow installation procedures as defined in method statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

Installation Procedure

1. Remove the release liner.
2. Apply the adhesive side of the tape onto the grey SikaProof®-808/-810 membrane surface.
3. Press the tape firmly along its length using a rubber or silicon hand pressure roller.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Limited (Vietnam)

Nhon Trach 1 Industrial Zone,
Nhon Trach Dist., Dong Nai Province,
Vietnam

Tel: (84-251) 3560 700

Fax: (84-251) 3560 699

sikavietnam@vn.sika.com



Product Data Sheet

SikaProof® Tape-120

May 2021, Version 01.01

020720308000000012

SikaProofTape-120-en-VN-(05-2021)-1-1.pdf