

PRODUCT DATA SHEET

Sarnatape®-20

Butyl rubber adhesive tape

DESCRIPTION

Sarnatape®-20 is a butyl rubber, double-sided adhesion sealing tape with a controlled stretch range.

USES

Sarnatape®-20 may only be used by experienced professionals.

- Metal deck sheet roofing and vertical wall panel sealing
- Jointing of protection boards/ various membranes

CHARACTERISTICS / ADVANTAGES

- Excellent anti-corrosive properties
- Easier installation due to easy peel.
- High durability, waterproof
- Self-amalgamating
- Green product, solvent free



PRODUCT INFORMATION

Chemical base	Adhesive Release liner	Butyl rubber Paper
Packaging	16 rolls in a box. Refer to current price list for packaging variations.	
Appearance / Colour	Smooth flat profile. Adhesive: Black	
Shelf life	2 years from date of production	
Storage conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +25 °C. Always refer to packaging.	
Length	10,00 m (± 1%)	
Width	50 mm (± 1%)	
Thickness	1,50 mm (± 1%)	

Mass per unit area	1,5 g/cm ³ (+20 °C)
Service temperature	-30 °C / max. +140 °C

APPLICATION INFORMATION

Ambient Air Temperature	Condition tape in application environment temperature before applying. For seams and detailing min. +5 °C / max. +40 °C
Substrate Temperature	+5 °C / max. +40 °C

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATION

- The use of Sarnatape®-20 is limited to geographical locations with average monthly minimum temperatures of -30 °C. Permanent ambient temperature during use is limited to +50 °C.
- The use of some ancillary products such as adhesives, cleaners and solvents is limited to temperatures above +5 °C. Observe temperature limitations in the individual Product Data Sheets.
- Special measures may be compulsory for installation below +5 °C ambient temperature due to safety requirements in accordance with national regulations.
- Stress-free bonding is required
- Do not use if exposed to permanent UV
- Do not use for bonding if subjected to mechanical loading

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

Sika Limited (Vietnam)
 Nhon Trach 1 Industrial Zone,
 Nhon Trach Dist., Dong Nai Province,
 Vietnam
 Tel: (84-251) 3560 700
 Fax: (84-251) 3560 699
 sikavietnam@vn.sika.com



Product Data Sheet
Sarnatape®-20
 June 2021, Version 01.02
 020945051200000004

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The contact surfaces must be secure, dry, clean and free of all contaminants such as dust, grease and other materials which could affect adhesion.

SUBSTRATE PREPARATION

All dust and loose particles must be completely removed from all surfaces before application of tape.

APPLICATION

Reference must be made to further documentation where applicable, such as relevant method statement, application manual and installation or working instructions.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sarnatape-20-en-VN-(06-2021)-1-2.pdf