

PRODUCT DATA SHEET

SikaProof® Sandwich Tape

DOUBLE-SIDED ADHESIVE TAPE, POLYACRYLATE-BASED

DESCRIPTION

SikaProof® Sandwich Tape is a double-sided adhesive tape consisting of a polyacrylic adhesive that is covered with a release liner.

USES

SikaProof® Sandwich Tape may only be used by experienced professionals.

SikaProof® Sandwich Tape is used for overlap jointing application in the SikaProof® A+ system.

CHARACTERISTICS / ADVANTAGES

- High adhesion of the polyacrylic adhesive
- High durability
- Easy and fast to install

PRODUCT INFORMATION

Packaging	5 rolls, packed in one cardboard box	
Appearance / Colour	White release liner over transparent polyacrylic adhesive	
Shelf life	18 months	
Storage conditions	SikaProof® Sandwich Tape rolls have a shelf life of 18 months from date of production, if stored properly in unopened, undamaged original packaging, in a horizontal position, in dry conditions and at temperatures between +5 °C and +25 °C. The rolls must be protected from UV radiation, rain, snow and ice, etc. Do not stack pallets of the rolls on top of each other or under pallets of any other materials during transport or storage.	
Dimensions	Width	50 mm
	Length	25 m
	Thickness	1,00 mm

SYSTEM INFORMATION

Compatibility	The surface to be bonded has to be solid, clean and dry. Contaminants, such as dirt, dust, oil, bitumen and de-bonding agents, such as surfactants and silicones have to be removed. For other material in direct contact (such as any synthetics etc.) the compatibility has to be evaluated.
----------------------	--

APPLICATION INFORMATION

Ambient Air Temperature -10 °C min. / +60 °C max.

Substrate Temperature +5 °C min. / +4 °C max.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The contact surface must be dry, clean and free of materials that could impair the adhesion.

APPLICATION METHOD / TOOLS

SikaProof® Sandwich Tape is a cold-applied double-sided adhesive tape for different detailing application. For further details about the installation method, refer to the SikaProof® A+ membrane product data sheet and method statement.

FURTHER DOCUMENTS

The SikaProof® A+ system must only be installed by trained and approved Sika contractors.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

ECOLOGY, HEALTH AND SAFETY

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Limited (Vietnam)

Nhon Trach 1 Industrial Zone,
Nhon Trach Dist., Dong Nai Province,
Tel: (84-251) 3560 700
Fax: (84-251) 3560 699
sikavietnam@vn.sika.com
vnm.sika.com



Product Data Sheet
SikaProof® Sandwich Tape
July 2019, Version 02.01
020704210220000020

SikaProofSandwichTape-en-VN-(07-2019)-2-1.pdf