

PRODUCT DATA SHEET

SikaWall®-720 E

DESCRIPTION

SikaWall® 720 E is a premium grade, polymer based internal skim coat that is available in paste form.

USES

SikaWall® 720 E is applicable to repair the decoration of the wall. Such as the wall potholes, small cracks, holes, peeling, nail holes, graffiti decoration.

CHARACTERISTICS / ADVANTAGES

- Ready to use
- Quick drying with high bond
- Spotlessly white and smooth

PRODUCT INFORMATION

Packaging	250g/piece
Shelf life	12 months
Storage conditions	+5°C~+25°C

TECHNICAL INFORMATION

Tensile Adhesion Strength	0.4Mpa
---------------------------	--------

APPLICATION INFORMATION

Substrates	Remove all dust, oil or traces of foreign materials.
------------	--

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATION

The working temperature is 5-30°C

The coating thickness should not exceed 0.5-1mm. (1 coat)

ECOLOGY, HEALTH AND SAFETY

APPLICATION METHOD / TOOLS

1. Fill in cracks with SikaWall® 720 E using knife;
2. Apply thin skin coat over the joint to prevent the

- edge from wrinkling;
3. Allow to dry before application of second coat;
 4. Apply finishing coat with trowel, use sand paper and hand sander to obtain a smooth surface.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Limited (Vietnam)

Nhon Trach 1 Industrial Zone,
Nhon Trach Dist., Dong Nai Province,
Vietnam

Tel: (84-251) 3560 700

Fax: (84-251) 3560 699

sikavietnam@vn.sika.com



Product Data Sheet

SikaWall®-720 E

September 2024, Version 01.01

021840303000000045

SikaWall-720E-en-VN-(09-2024)-1-1.pdf