

## PRODUCT DATA SHEET

# SikaProof®-936

(formerly MSeal 936)

Double-sided sticky tape for SikaProof®-730 PA HDPE pre-applied waterproofing system

## DESCRIPTION

SikaProof®-936 is a white or light yellow double sided sticky, HDPE self-adhesive tape for SikaProof®-730 PA HDPE pre-applied waterproofing system.

## USES

It is designed for use in underground waterproofing termination detailing along with SikaProof®-730 PA membrane system.

SikaProof®-936 is used for end lap treatment as part of the SikaProof®-730 PA membrane system.

SikaProof®-936 is applied to waterproofing and damp-proofing engineering's for various underground building structures and basements.

## CHARACTERISTICS / ADVANTAGES

The specially-made high density thermoplastic polyethylene (HDPE) film works as a waterproof base material. On both sides the HDPE film is covered with macromolecule self-adhesive film and on the exposed surface the composite adhesive. The weather-resistant protective and insulating layer, belongs to macromolecule self-adhesive film.

## PRODUCT INFORMATION

<b>Packaging</b>	Rolls of 80mm (width) x 50m (length)
<b>Shelf life</b>	12 months from date of production if stored properly in unopened, original packaging.
<b>Storage conditions</b>	Store in dry conditions between +5 °C to +30 °C. Rolls must be stored in their original package, under cool and dry conditions. Protected from direct sunlight, rain, snow and ice.
<b>Thickness</b>	0.3 mm

## TECHNICAL INFORMATION

<b>Tensile Strength</b>	800 N/50mm
<b>Elongation at break</b>	500 %
<b>Adhesion in Peel</b>	1.5 N/mm (To concrete after 28 days water immersion)
<b>Joint Shear Resistance</b>	<b>Shear Strength:</b> 5 N/mm (GB/T 328.23)

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

## APPLICATION INSTRUCTIONS

SikaProof®-936 is part of the SikaProof®-730 PA system, please refer to the relevant method statement or contact our Sika representative for further support.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Sika Limited (Vietnam)

Nhon Trach 1 Industrial Zone,  
Nhon Trach Dist., Dong Nai Province,  
Vietnam

Tel: (84-251) 3560 700

Fax: (84-251) 3560 699

sikavietnam@vn.sika.com



### Product Data Sheet

SikaProof®-936

September 2024, Version 02.01

02072000000002008

SikaProof-936-en-VN-(09-2024)-2-1.pdf