

PRODUCT DATA SHEET

SikaProof® Tape A+ N

Self-adhesive tape for internal jointing of SikaProof® A+ waterproofing system.

DESCRIPTION

SikaProof® Tape A+ N is a self-adhesive tape based on a polyacrylate adhesive with a carrier film and a release liner.

USES

The Product is used for:

- Sealing and bonding overlap joints, connections and details within the SikaProof® A+ system, including SikaProof®-808.

CHARACTERISTICS / ADVANTAGES

- Fully and permanently bonded to the concrete structure
- No lateral water underflow between the concrete structure and the membrane system
- High adhesion and good sealing capacity in cold and damp conditions
- Fast and easy to install

PRODUCT INFORMATION

Packaging	4 rolls packed in one cardboard box	
	Roll length	25 m
	Roll width	(120 ± 5) mm
Shelf life	18 months from date of production	
Storage conditions	The Product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +30 °C. Always refer to packaging.	
Appearance / Colour	Top layer	Light grey hybrid bonding layer with yellow waterproofing layer
	Bottom layer	Transparent polyacrylate adhesive covered with transparent release liner
Thickness	~1.6 mm (+0.17 mm / -0.08 mm)	

APPLICATION INFORMATION

Ambient Air Temperature	Maximum	+45 °C
	Minimum	+5 °C
Substrate Temperature	Minimum	+5 °C

SYSTEM INFORMATION

System Structure

SikaProof® Tape A+ N is a system component for internal jointing of the SikaProof® A+ and SikaProof®-808 systems. For more detailed information, refer to Sika® Method Statement: Method Statement SikaProof® A+ and SikaProof®-808.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER DOCUMENTS

Refer to the following Sika® Method Statements:

- Method Statement SikaProof® A+/ SikaProof®-808
- Application manual SikaProof® A+/ SikaProof®-808

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The contact surface is the grey SikaProof® A+/ SikaProof®-808 bonding layer. It must be dry or slightly damp, clean and free of any materials that could impair adhesion.

Application outside of specified application conditions

Note: Under certain circumstances, the Product can be applied in conditions other than the ones specified in this data sheet. However, this requires specific precautions and application methods.

1. Contact Sika technical services for more information.

Sika Limited (Vietnam)

Nhon Trach 1 Industrial Zone,
Nhon Trach Dist., Dong Nai Province,
Vietnam

Tel: (84-251) 3560 700

Fax: (84-251) 3560 699

sikavietnam@vn.sika.com



Product Data Sheet

SikaProof® Tape A+ N

August 2024, Version 02.01

020720308000000021

APPLICATION

IMPORTANT

Strictly follow installation procedures

Strictly follow installation procedures as defined in Method Statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

IMPORTANT

Application by trained personnel

The application of this Product must only be carried out by an applicator that is trained or approved by Sika. The applicator must also be experienced in this type of application.

IMPORTANT

Exposure to UV or weathering

The Product is not resistant to permanent UV exposure or weathering.

1. Protect as soon as possible but not later than 90 days after application
1. Remove the release liner
2. Apply onto the grey SikaProof® A+/ SikaProof®-808 membranes side
3. Press on firmly using a pressure roller

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SikaProofTapeA+N-en-VN-(08-2024)-2-1.pdf